TECHNICAL DATASHEET

PRIME
Quality Commercial Lighting


AL-LPUD40 Range
ARCHITECTURAL SUSPENDED LINEAR INDIRECT-DIRECT LIGHT




PRODUCT FEATURES

- Connectable up to 8 units
- Includes Cover Plate
- Laser Etched Light-Guide
- Edge Lit (no glare)
- Excellent Uniformity
- Lightweight Aluminum Construction
- 4200 lm, 55% Down & 45% Up
- UGR Rating <19
- 50,000 hrs DLC approved 5 Year Warranty
- Suspension 51.2" (Adjustable)

Connectable



DIMENSIONS



Dual Light Distribution

5 Year Warranty

Product	AL-LPUD40/35K	AL-LPUD40/40K	AL-LPUD40/50K
Dimmable	0-10V Dimmable	0-10V Dimmable	0-10V Dimmable
Voltage	100 -~ 277v AC	100 - 277v AC	100 - 277v AC
Watts	40W	40W	40W
Lumens	≤4200 lm	≤4200 lm	≤4200 lm
Color Temp	3500K	4000K	5000K
Life (hrs)	50,000 hrs	50,000 hrs	50,000 hrs
Suspension	51.2" (Adjustable)	51.2" (Adjustable)	51.2" (Adjustable)
L x W x H	47.24' x 7.87' x 0.94'	47.24' x 7.87' x 0.94'	47.24' x 7.87' x 0.94'

© All Right Reserved ALL-LED USA LLC,
www.all-ledusa.com
info@all-ledusa.com
+1 727 524 4270
+1 727 290 3914