
TECHNICAL DATASHEET


AL-SM RANGE

Surface Mount Round Mini-Panel Range



PRODUCT FEATURES

- Low Profile Design
- Dimmable on most leading / trailing edge 120V Dimmers
- Lightweight Aluminium Body with Polymer Diffuser
- White Bezel
- Lifetime 50,000hrs
- 5 Year Warranty
- Low Glare



≤700 lumens | ≤1100 lumens | ≤1800 lumens | Quality Assured

Dim | 50,000 HRS lifetime | 10W | 15W | 20W | WARM WHITE 3000K

Intertek 4008281 | CRI 90 | ENERGY STAR | CALIFORNIA JA8 TITLE 24 COMPLIANT LAMP

DAMP LOCATIONS | FC | 5 Year Warranty

PRODUCT CODE	AL-SM5R10/30	AL-SM7R15/30	AL-SM9R20/30
CONSUMPTION	10W	15W	20W
LUMENS	≤700lm	≤1100lm	≤1800lm
BEAM ANGLE	100°	100°	100°
CCT	3000K	3000K	3000K
CRI	>90	>90	>90
LIFETIME	50,000hrs	50,000hrs	50,000hrs
OPERATING TEMPERATURE	-4 ~ +113°F	-4 ~ +113°F	-4 ~ +113°F
VOLTAGE	100-277V	100-277V	100-277V
WARRANTY	5 Years	5 Years	5 Years
DIMMING	120v Line Voltage	120v Line Voltage	120v Line Voltage

© All Right Reserved ALL-LED USA LLC,
www.all-ledusa.com
info@all-ledusa.com
+1 727 524 4270
+1 727 290 3914