

4FT



T8 LED

Luminous Efficiency Redefined

3500K

4000K

5000K


AL-T8LED15AB - WORKS WITH OR WITHOUT BALLAST

4ft T8 Led Tube Type A+B 15W 1900lm Shatter Proof

PRODUCT FEATURES

- Type A and B – works with or without a ballast, 3 in one ballast compatible
- Plug and play direct with ballast
- Double-ended ballast bypass for direct wire
- Shatterproof design meets NSF requirements.
- Life span 50,000HRS
- 5 years warranty

Dimension



Length: 4FT



Product Code	AL-T8LED15AB/35	AL-T8LED15AB/40	AL-T8LED15AB/50
Input Voltage	120~277V AC	120~277V AC	120~277V AC
Dimmable	No	No	No
Operating Temp	-4°F - 104°F	-4°F - 104°F	-4°F - 104°F
Wattage	15W	15W	15W
Material	Shatterproof Glass	Shatterproof Glass	Shatterproof Glass
Lamp Base	G13	G13	G13
Lifetime L70 (hrs)	50,000 hrs	50,000 hrs	50,000 hrs
Input Frequency	50/60HZ	50/60HZ	50/60HZ
Location Information	Damp Location	Damp Location	Damp Location
Power Factor	0.95	0.95	0.95
Beam Angle	320°	320°	320°
Lumens	≤1900 lm	≤1900 lm	≤1900 lm
CCT	3500K	4000K	5000K
CRI	>80	>80	>80