






AL-CL406070CCT

Canopy Light - CCT & Wattage Selectable

PRODUCT FEATURES

- Suitable for use on exterior warehousing, industrial, and commercial buildings
- Significant energy savings and maintenance free
- 0-10V dimming with most 0-10V dimmers
- IK08 polycarbonate lens with 155° beam angle
- Instant on/off, no re-strike delay
- AC100-277 volts
- Suitable for wet locations IP65
- Power selectable 40W/60W/70W
- CCT selectable 3000K, 4000K, 5000K
- (L70) at 50,000 hours lifetime
- WITH MICROWAVE SENSOR (button type photocontrol)

Dimensions



ACCESSORIES

AL-CLPC - Sensor

Product Code	AL- CL406070CCT
Power	40W / 60W / 70W
120 Lumens Per Watt	4800LM / 7200LM / 8400LM
Color Temperature	CCT Selectable (3000K / 4000K / 5000K)
Net Weight	5.95lbs
Input Voltage	100-277V AC
Power Factor	0.90
LED Type	SMD
CRI	>80
Location Information	Wet Location
Warranty	5 Years
Operating Temperature	-40°F~122°F
Beam Angle	155°
Frequency	50/60hz
Dimming Protocol	0-10V
Body Material	Die-Cast Body, polycarbonate Lens
Impact Resistance	IK08



Email us at info@all-ledusa.com

www.all-ledusa.com